## **C**ONDUCTIVITY INSTRUMENTS



## **Conductivity and Salt % Calibration Solutions**



- Ideal for Calibrating All Conductivity Instruments
- 4 Popular Ranges Available for Fast Delivery
- NIST Certificate of Conformance Optional

Conductivity solutions are used for calibrating most of the conductivity instrumentation shown in this section. To calibrate an instrument, select a conductivity solution that is close to the measuring range and calibrate the instrument for optimal system accuracy.

**Note:** Calibration of conformance certification available at time of purchase. Add suffix "-CAL-CDS" to model number for additional cost, and set-up charge to order.

\* 6 month shelf life.

Ordering Examples: CDSA-1500, 1500 μS/cm conductivity solution. CDSA-450, 450 μS/cm conductivity solution.

To Order	
Model No.	Description
CDSA-10*	10 μS/cm conductivity solution
CDSA-15*	15 μS/cm conductivity solution
CDSA-45	45 μS/cm conductivity solution
CDSA-450	450 μS/cm conductivity solution
CDSA-1413	1413 μS/cm conductivity solution
CDSA-1500	1500 μS/cm conductivity solution
CDSA-4500	4500 μS/cm conductivity solution
CDSA-15000	15000 μS/cm conductivity solution
CDSA-45000	45000 μS/cm conductivity solution
CDSA-1-NACL	1% NaCl solution
CDSA-10-NACL	10% NaCl solution
PHA-77	Third-arm electrode holder